

# 930 Series Miniature Bayonet Relampable Lampholders Ø 0.691" (17.5mm)



Relampable lampholders accommodate T-3 1/4 and T-2 incandescent lamps and T-3 1/4 neon lamps















### **Applications**

- · panel indication
- electrical panels
- entertainment
- industrial


- appliances
- displays

#### **Key Features**

- For panel hole diameter: 0.691" (17.5mm)
- Terminations available: solder lug, screw type or wire leads
- Variety of connection options for fast, easy installation.
- Can be mounted in D shaped holes
- Resistors are available in order to adjust the brightness
- Acommodate T-3 1/4 and T-2 incandescent lamps and T-2 neon lamps

- Available in seven lenses colors (red, green, white, blue, clear, amber and yellow).
- · Robust lampholder assembly
- Drip proof option
- Finish available (lampholders): e-coat black,
  bright nickel, satin chrome or polished chrome
- Lead wire options with custom wire length available.
- · RoHS and REACH Compliant.

#### **Ordering Data**



Lampholders and Lens Caps may be ordered separately or as complete assemblies as shown in the example below

## 930424X897RD



Lens

Color

(Red

Diffusing)

Retainer

(Polished


Chrome)


# **Product Specifications**

Materials	
Housing	Brass. E-coat black, bright nickel, polished or satin chrome finishes
Body	High dielectric phenolic
Lockwasher	Phospor bronze. Nickel-plated
Lens	Heat resistant, polycarbonate See notes 7 and 8 on page 2
Hex Nut	Brass. Nickel plated.
Terminals	Solder Lug: Brass, tin plated Screw Type: 4-40 brass, nickel plated binding head screws
Wire Leads	6" Leads, #18 AWG, black & white stranded cooper, PVC insulated, UL/CSA rated 105°C, stripped 1/2". Custom wire options are also available
Retainer	Brass. Zinc plated, bright nickel, polished or satin chrome finishes

Installation Specifications		
Mounting Hole	.651"±.005 (16.5mm±.1)	
D- mounting	.651"±.005 (16.5mm±.1) x	
hole (optional)	.691"±.003 (17.6mm±.1)	
Maximum Rating	3 Watts, 250 Volts	

# **Mounting Holes - Dimensions**





OPTIONAL "D" MOUNTING HOLE

All Dimensions in inches [mm]


# **Compliance and Approvals**







# **Product Dimensions - Housing and Termination**


# Screw Type






# Solder Lug





#### Wire Leads



All Dimensions in inches [mm]

## **Product Dimensions - Lens Style**


### Lens Style - Retainer Required


Flat:


Flat Drip Proof:


Convex:

Convex Drip Proof:











## Lens Style - No Retainer Required


Dome:

.440 [11.2] 9/16-27UNS-2A





Dome Fluted:






Cylindrical:






Cylindrical Fluted:






Lens Style - Lampholder features Drip-proof (with O-Ring)


Dome:




Dome Fluted:



Cylindrical:



Cylindrical Fluted:



All Dimensions in inches [mm]