Chip Beads (2512061017Y0)



Part Number: 2512061017Y0

MULTI- LAYER CHIP BEAD

Part Number System: Example 2512063017Y1

25	1206 301		7	Y	1		
Chip	Chip Package Imped		Packaging	Material	Current Code		
Bead	Size	Code	Code	Code	0 < 1.0A		
Code	Code	300 A	6= Bulk Packed	Y = Standard Signal Speed	1 ≥1.0A <2.0A		
		7=	Taped and Reeled 7" Reel	Z = High Signal Speed	3 ≥ 3.0A < 4.0A		
		8=	Taped and Reeled 13" Reel	H = GHz Speed	ETC		

Fair- Rite offers a broad selection of cost effective multi- layer chip beads to suppress conducted EMI signals. Chip beads can be used in an array of devices such as cellular phones, computers, laptops, pagers, etc. The small package sizes accommodate automated placements and allow for a dense packaging of circuit boards.

Chip Beads are available in standard, high and GHz signal speeds.

Packaging Options:

- All multi- layer chip beads are supplied taped and reeled, if required bulk packed chip beads can be provided.

The suggested land patterns are in accordance to the latest revision of IPC-7351.

<u>Weight:</u> 0.03 (g)

Package Size: 1206 (3216)

Раскар	ge Size:	1206 (3216	5)							
Dim	mm	mm tol	nominal inch	inch misc.		Reel Information				
A	1.1	±0.20	0.043	_		Tape Width	Pitch	Parts 7"	Parts 13"	Parts 14"
В	1.6	±0.20	0.063			mm	mm	Reel	Reel	Reel
С	3.2	±0.20	0.126			8	4	3000	10000	_
D	0.7	±0.30	0.028							
Land I	atterns		•			hart Legend				
V		W	Х	Y	Z	Test frequency	1			
1.20 (0.047	")	2.80 (0.110")	1.80 (0.071")	1.60 (0.063")	_					
Туріса	l Impe	dance (Ω)								
50 MH	Iz 7	2								
100 M	Hz^+ 1	00 ±25%								
500 M	Hz 1	27								
1000 N	MHz^+ -									

Electrical Properties					
Max DCR (Ω)	0.2				
Max Current (mA)	450				

The impedance values listed are typical values. The nominal impedance with a +/- 25% tolerance is specified for the + marked 100 MHz. Chip beads are measured for impedance on the HP 4291A and fixture HP 16192A. Chip beads are 100% tested for impedance and dc resistance.

Fair- Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288 888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair- rite.com • www.fair- rite.com